


JLG M3369LE

HYBRID ELECTRIC SCISSOR LIFT

alfasi hire



alfasi hire

1300 55 1108

www.alfasihire.com.au

QUESTIONS TO ASK

- What are the ground conditions in the work area?
- What is the rated capacity needed for the job?
- Do you need an extension lead outlet in the platform?
- Do you need non-marking tyres?
- Is there power available on the site?

KEY SELLING POINTS

- Smooth control, proportional electric drive, with two speed ranges
- Oscillating rear axle for constant rear wheel traction
- Fold-down rails allows drive through standard 203cm door
- Extension platform has fold-down rails
- Non-marking urethane filled tyres
- Constant traction 2 wheel drive for 35 per cent gradeability
- Wide scissor stack provides rigidity and stability
- Multi axis 4 degree level sensor
- Plug in JLG analyser to indicate system functions for servicing and adjustment
- Removable platform control box
- Kubota single cylinder diesel engine to operate 55 Amp Mechtron charger when battery voltage drops below a prescribed level, charge on the go

APPLICATIONS

- Facilities maintenance
- Shopping centres and other indoor/outdoor areas
- Manufacturing and warehouse applications and stock-takes
- Electricians
- Plumbers
- Window installers
- All maintenance and construction work
- Factory fit outs before electrical power is connected

SPECIFICATIONS

Performance:

Platform Height (max.)	10.06m
Working Height	12.06m
Lift Time	38 sec
Lower Time	42 sec
Platform Capacity Standard	450kg

Dimensions:

Stowed Height - Rails Up	2.74m
Stowed Height - Rails Lowered	1.98m
Minimum Transport Length (outriggers)	3.07 (3.81)m
Overall Width	1.75m
Wheelbase	2.32m
Ground Clearance	0.20m
Platform Width	1.65m
Platform Length	2.92m
Standard Platform Extension	0.91m
Stabiliser Levelling - Fore and Aft	Auto
Stabiliser Levelling - Side to Side	Auto/Manual
Platform Height Lowered	1.69m
Maximum Drive Height	10.06m

Power:

Power Source	Battery
Engine Make	Kubota
Engine Model	OC 60
Engine Power	4.5kW
Engine Fuel	Diesel
DC Voltage	48V
DC Power	370 Amp h
Genset	55 Amp
Drive Motors - Type	DC Electric
Hydraulic Pump - Type	Gear
Batteries	8 x 6V
Generator Set	Kubota
Generator Set Fuel Tank Capacity	15 Ltr

Travel:

Tyre Size	240/55-17.5
Tyre Type	Foam Filled/Non-marking
Inside Turn Radius	2.29m
Outside Turn Radius	4.88m
Drive Speed Elevated	0.64km/h
Gradeability	35%

Weights and Capabilities:

Hydraulic Tank Capacity	32 Ltr
Operating Weight	5,250kg