



**2684RT/3084RT**  
ROUGH TERRAIN SIGMA LIFTS

**alfasi hire**



**Construction Grade  
Rough Terrain  
Speed Level™  
Sigma Lifts**

**Model**  
**2684RT SPEED LEVEL™**  
**3084RT SPEED LEVEL™**

- Up to 36 ft. (11m) working height
- Fast platform leveling on slopes, automatic or manual selection, with an amazing 14° side to side and 10° fore and aft oscillation
- Up to 1,700 lbs (770 kg) platform capacity
- Quad-Trax 4wd power package giving 45% gradeability
- Proportional drive and lift controls
- Non-skid metal deck construction
- Large sheet loading entrances (fore and aft)
- No-maintenance bearings
- Multiple power selections (gasoline/liquid propane or diesel)
- Incredible ground clearance

**alfasi hire**

**1300 55 1108**  
**www.alfasihire.com.au**



# 2684RT/3084RT

ROUGH TERRAIN SIGMA LIFTS

# alfasi hire

## Features

### Work Area

Automatic and Manual Platform Leveling  
Large sheet loading entrance accommodates 48" (1.22 m) material  
110V Power to Platform

### Performance

Proportional Drive and Lift Controls  
High Torque Power Package

### Engine

Kubota Engine (Gasoline/Liquid Propane)

### Serviceability

Lubrication-Free Bearings  
Easy maintenance access to mechanical and electrical components  
Logically grouped components and numbered wiring for easy reference

### Safety

Dedicated compartments protect electrical and hydraulic components  
Emergency shut-off at platform and lower controls  
Non-Skid Metal Deck Construction  
Motion Alarm  
Drive Speed Interlock  
Multi-Axis Tilt Sensor  
Multiple Disc Brakes, Manual Brake Release  
Dual Automatic Parking Brake

### Other Features

Platform Swing Gate  
Fold-down Guardrail  
Hour Meter  
Powder Coat Finish  
Machine Tie Downs

## Optional Features

Lanyard Attachments (6)  
Flashing Beacon (continuous)  
Quad-Trax 4wd Power Package  
Automotive Horn  
Removable Upper Controls  
Air Line to Platform  
Audible Motion Alarm  
Kubota D1105 Diesel Engine  
Generator  
Foam-Filled Tires  
Non-Marking Tires  
Turf Tires  
CE Compliant Options  
Australian Compliant Options  
CSA Compliant Options  
1 or 2 Year Extended Warranty

Model	2684RT Speed Level™		3084RT Speed Level™	
	U.S.	Metric	U.S.	Metric
<b>Heights</b>				
Working Height*	32 ft.*	9.75 m*	36 ft.*	11 m*
Platform Height	26 ft.	7.93 m	30 ft.	9 m
Maximum Drive Height	26 ft.	7.93 m	30 ft.	9 m
Stowed Height (Top Guardrail)	105 in.	2.67 m	105 in.	2.67 m
Stowed Height (Rails Folded)	70 in.	1.78 m	70 in.	1.78 m
Guardrail Height	43½ in.	1.1 m	43½ in.	1.1 m
Toeboard Height	6 in.	15 cm	6 in.	15 cm
Ground Clearance	10 in.	25 cm	10 in.	25 cm
<b>Dimensions</b>				
Length - Stowed (Overall)	12 ft. 6 in.	3.8 m	14 ft. 6 in.	4.4 m
Width	84 in.	2.13 m	84 in.	2.13 m
Platform Length	12 ft.	3.65 m	14 ft.	4.27 m
Platform Length (Extended)	15 ft.	4.57 m	-	-
Platform Width	72 in.	1.83 m	72 in.	1.83 m
Wheelbase	100 in.	2.54 m	100 in.	2.54 m
Lift Capacity	1,700 lbs.	770 kg	1,500 lbs.	680 kg
Extension Deck Lift Capacity	500 lbs.	227 kg	-	-
Structure Leveling	14° side to side, 10° fore and aft		14° side to side, 10° fore and aft	
<b>Speeds</b>				
Raise/Lower Speed	25/35 sec.		30/40 sec.	
Drive Speed (Stowed)	4 mph	6.4 km/h	4 mph	6.4 km/h
Drive Speed (Raised)	.4 mph	.6 km/h	.4 mph	.6 km/h
<b>Performance</b>				
Gradeability	45%/24.2°		45%/24.2°	
Turning Radius (Inside)	8 ft.	2.44 m	8 ft.	2.44 m
Turning Radius (Outside)	16 ft. 8 in.	5.08 m	16 ft. 8 in.	5.08 m
Weight **	7,500 lbs**	3400 kg**	7,500 lbs**	3400 kg**
Brakes	Dual rear wheel multi-disc			
Power Source	Kubota DF752 Dual Fuel		Kubota DF752 Dual Fuel	
Controls	Proportional			
Tires	26 X 12D / 380NHS			
Fuel Capacity	15 gal.	57 L	15 gal.	57 L
Hydraulic Fluid Capacity	23 gal.	87 L	23 gal.	87 L

\*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.

\*\*Weight may vary with certain options or configurations. When platform is elevated, all models must be on a firm, planar surface.

# alfasi hire

1300 55 1108  
www.alfasihire.com.au