

**MERLO**  
AUSTRALIA

**P36.10**

TELEHANDLER

**alfasi hire**



**PANORAMIC**


**alfasi hire**

**1300 55 1108**

[www.alfasihire.com.au](http://www.alfasihire.com.au)

PANORAMIC	RIGID FRONT AXLE		SIDE-SHIFT + FRAME LEVELLING		
	P 34.7 P 34.7 PLUS	P 34.10 P 34.10 PLUS	P 36.7 P 36.7 PLUS	P 36.10 P 36.10 PLUS	
<b>Weight</b>					
Total empty weight (with forks)	kg	6600	7250	6760	7350
<b>Performance</b>					
Rated maximum load	kg	3400	3400	3600	3600
Maximum lift height	m	7	9.7	7	9.7
Maximum forward reach	m	3.65	6.2	3.65	6.2
Lift height at full capacity	m	7	5.5	7	8
Reach at full capacity	m	1.5	1.6	1.5	1.6
Capacity at full lift height	kg	3400	1200	3600	3000
Capacity at full forward reach	kg	1350	600	1350	600
Low emission (Euro 2) turbo engine		turbo	turbo	turbo	turbo
Power at 2400rpm (97/68/CE)	kW/HP	74.9/102	74.9/102	74.9/102	74.9/102
<b>Speed ratios</b>					
1 <sup>st</sup> gear	kph	7/11 <sup>(1)</sup>	7/11 <sup>(1)</sup>	7/11 <sup>(1)</sup>	7/11 <sup>(1)</sup>
2 <sup>nd</sup> gear (self-limiting maximum speed)	kph	25/40 <sup>(1)</sup>	25/40 <sup>(1)</sup>	25/40 <sup>(1)</sup>	25/40 <sup>(1)</sup>
<b>Dimensions</b>					
A	mm	4180	4340	4300	4340
B	mm	905	1060	980	1010
C	mm	2700	2700	2750	2750
D	mm	570	570	570	570
E	mm	3865	3865	3915	3915
F	mm	565	565	565	565
H	mm	2230	2230	2230	2230
M	mm	995	995	995	995
P	mm	2475	2475	2475	2475
R	mm	3985	3985	4050	4050
S	mm	4670	4850	4800	4850
Z	mm	850	850	850	850

<sup>(1)</sup> 11kph and 40kph are the maximum speed ratios in PLUS models



<sup>(1)</sup> Internal width

